

Metric ProStack DRL Pallet

PI012DRL



- Telescoping Double legs provide twice the forklift damage protection of common single walled pallets.
- High-density polyethylene structural foam that resists mold, bacteria and insect infestation.
- Anti-microbial additive options available
- Highly Durable and easy to clean
- Unique Lower Deck Design includes first ever pallet jack guide that prevents related damage
- Edge Rackable to 1,000 kg
- Fire Retardant—FM Approved Non-deca BDE
- 4-way Entry for forklift and pallet jacks
- Ideal for Pharmaceutical, Medical, Industrial, Food and Beverage applications.
- Optional Intermittent perimeter lip
- Optional Molded-in or hot stamped logo/company ID
- Optional Grommets

Model	P41012DRL
Entry	4-Way
Material	PE
Secondary Support	None
Length	1200 mm
Width	1000 mm
Height	160 mm
Weight	21 kg
Static Load Rating	13,636 kg
Dynamic Load Rating	2,273 kg
Edge Rack Load Rating	1,000 kg
Supported Racking Rating	2,273 kg
Truckload	53' - 510 13.5 m - 510
Ocean Container	40' HC-340

Distributed by:
 TMF Corporation
 850 West Chester Pike, Suite 303
 Havertown, Pennsylvania 19083-4442

Phone: 866-713-9446
 Fax: 610-789-5168
 E-mail: info@tmfcorporation.com

10/2013

