

# Metric ProStack DRL Solid Top P1012DRL-SD



- Solid Top prevents loose product from falling through open grid.
- Telescoping Double legs provide twice the forklift damage protection of common single walled pallets.
- Innovative Ratchet Fastening System: 3 times stronger than welded or snap construction
- Can be made to be Edge Rackable to 1,000 Kg.
- Anti-microbial additive options available.
- Highly Durable, Easy to Clean and Hygienic
- Unique Lower Deck Design includes first ever pallet jack guide that prevents related damage
- 4-way Entry for forklift and pallet jacks
- Ideal for Pharmaceutical, Medical, Industrial, Food and Beverage applications.
- Optional Intermittent perimeter lip
- Optional Hot Stamped
- Open deck available



Model	P1012DRL-SD
Entry	4-Way
Material	PE
Secondary Support	None
Length	1200 mm
Width	1000 mm
Height	160 mm
Weight	22 kg
Static Load	13,636 kg
Dynamic Load	2,273 kg
Edge Rack Load	1,000 kg
Supported Racking	2,273
Pack out	53' Truck: 510 40' HC: 340

Distributed by:  
TMF Corporation  
850 West Chester Pike, Suite 303  
Havertown, Pennsylvania 19083-4442

Phone: 866-713-9446  
Fax: 610-789-5168  
E-mail: [info@tmfcorporation.com](mailto:info@tmfcorporation.com)

10/2013

